

# LANSEN

Temp/Humidity/Radon/Pressure

LAN-MIOTY-Q-R

## DEVICE

The Q-series sensor from Lansen continuously measures important indoor parameters. It is plug-and-play and can be mounted in any room where there is a need to know the radon, pressure, temperature and humidity level. The device has a sleek and discrete design and blend nicely in any office or home environment.

## PERFORMANCE

The internal radio antenna is optimized for 868Mhz and is tuned for mounting on concrete, wood or plaster.

## MEASUREMENTS

Sensor parameters are sent every 60 seconds using the mioty protocol. This makes the sensor ideal for integration in data collecting systems or drive by solutions.

All parameters are updated every 60 seconds except the radon level which is updated every 10 minutes.

## FIRMWARE

MODES mioty ETSI TS-103-357  
ENCRYPTION Network: AES128 encryption

## INTERVAL

TRANSMISSION Every 60 seconds.  
SAMPLE  
Radon 10 minutes.  
All other parameters Same as transmission interval.

## MIOTY DATA

(TBD)  
TEMPERATURE Last measured temperature.  
HUMIDITY Last measured humidity.  
RADON Last measured radon.  
RADON READY Radon sensor working normally.  
RADON ERROR Radon module error.  
PRESSURE Last measured pressure.

## POWER/LIFETIME

POWER SUPPLY  $24 \pm 20\%$  VAC or VDC (adapter not included)  
RADIO 16 dBm (25 mW) output power  
ERP typical: 10.7 dBm (11.75 mW)

## GENERAL INFORMATION

STANDARDS 2014/53/EU (RED)  
COLOR Signal white  
MATERIAL ABS/PC Front, ABS back.  
SIZE (W x H x D) 142 x 142 x 40 mm

## OPERATING CONDITIONS

RADIO TRANSMITTER Max: 0°C to +85°C  
Recommended: +5°C to +50°C

## RADON SENSOR

The radon sensor is a high performance radon sensor that measures the decay of radon particles. The radon value is updated as often as every 10 minutes and this fast response time allows the device to be used even in HVAC system.

## TEMPERATURE SENSOR

The on-board temperature sensor is highly accurate with typical accuracy  $\pm 0.5^\circ\text{C}$ .

## HUMIDITY SENSOR

The on-board humidity sensor is highly accurate in the entire temperature range, with typical accuracy  $\pm 2\%RH$ .



# LANSEN

Temp/Humidity/Radon/Pressure/CO<sub>2</sub>

LAN-MIOTY-Q-series

## DEVICES

Name	Temperature	Humidity	Pressure	Radon	CO <sub>2</sub>	24 VDC or 24 VAC
LAN-MIOTY-Q-RC	X	X	X	X	X	X
LAN-MIOTY-Q-C	X	X	X		X	X
LAN-MIOTY-Q-R	X	X	X	X		X

## SENSORS

Type	Range	Typical accuracy	Sample intervall	Operating condition
TEMPERATURE	-40°C to +85°C	±0.5°C at -20°C to +85°C	60 sec	Non condensing
HUMIDITY	0 - 100 %RH	±2 %RH at 20-80 %RH. ±3 %RH at 10-90 %RH ±3,5 %RH at 0-100 %RH	60 sec	Non condensing
CO <sub>2</sub>	0-5000 ppm	±(50 ppm+3%) after calibration	60 sec	<u>Temperature:</u> 0°C to +55°C (-20°C to +55°C on request) <u>Pressure:</u> 950 mbar to 1050 mbar (other range on request) <u>Humidity:</u> %RH < 90% and non condensing)
RADON	Sensitivity: 0.3cpm/pCi/L (11,1 Bq/m <sup>3</sup> ) Range: 0.2 ~ 99.9pCi/L (7~3,700Bq/m <sup>3</sup> )	< ±15% Min. uncertainty: 26 bq/m <sup>3</sup>	10 minutes	Temperature: 10°C to +50°C Humidity: %RH < 80 and non condensing
PRESSURE	300 to 1200 hPa	± 2 hPA	60 sec	Temperature: -30°C to +85°C